



Hand Pallet Truck

BF

INNOVATION DESIGN

Reduce maintenance cost > Improve working efficiency > Increase truck service life

- High reliability, suitable for a variety of environments. It can be used for 3~5 years under normal maintenance.
- The first design of forging & casting integral pump, which prevents any loosening and leakage.
- High-strength alloy steel carefully rafted, increased loading capacity.
- Set the active safety valve to prevent overloading of operation.
- 54mm fork thickness ensures high capacity.
- Optimized round fork tips ensure easy operation;
- Curve design on the fork tips helps pallets entry in/out.
- With copper bushin, no need to add grease, reduce maintenance cost.

SPECIFICATION

Specification	1	Model		BF		
	2	Capacity	kg	2500	3000	3500
	3	Steering wheel size	mm	180×50	180×50	180×50
	4	Fork wheel tandem	mm	80×70/74×70	80×70/74×70	80×70/74×70
	5	Fork wheel single	mm	80×93/74×93	80×93/74×93	80×93/74×93
	6	Max. Lifting height	h3(mm)	200/190	200/190	200/190
	7	Lowered height	h13(mm)	85/75	85/75	85/75
	8	Overall length	l1(mm)	1534/1604	1534/1604	1534/1604
	9	Fork dimensions	s/e/l(mm)	54/160/1150(1220)	54/160/1150(1220)	54/160/1150(1220)
	10	Width overall forks	b5(mm)	520/550/685	520/550/685	520/550/685
	11	Turning radius	Wa mm	1249/1319	1249/1319	1249/1319
	12	Aisle width, with pallet 1000x1200 crosswise	Ast(mm)	1683/1716/1786	1683/1716/1786	1683/1716/1786
	13	Aisle width, with pallet 800x1200 lengthwise	Ast(mm)	1783/1816/1886	1783/1816/1886	1783/1816/1886
	14	Ground clearance, centre of wheelbase	m2(mm)	32	32	32
	15	Height of tiller in drive position max	h14(mm)	1224	1224	1224

