



CDD15K/20K ELECTRIC STACKER

Specification	1	Model		CDD15K/CDD20K	
	2	Operating Type		Stand on	
	3	Power Type		Electric	
	4	Load Capacity	kg	1500/2000	
	5	Load Center	c(mm)	600	
	6	Wheel Type		Polyurethane	
	7	Wheelbase	y(mm)	1355	
	8	Wheel Size,front	mm	Φ 250×75	
	9	Wheel Size,rear	mm	Φ 80×70	
	10	Additional wheel	mm	Φ 115×50	
	11	Thread,rear	b11(mm)	570/685	
Dimensions	12	Lowered Mast Height	h1(mm)	2085/1765/2015/2165/ 2330/2000/2170/2340	
	13	Max.lifting Height	h3(mm)	1600/2500/3000/3300/ 3500/4500/5000/5500	
	14	Extended Mast Height	h4(mm)	2085/3050/3550/3850/ 3950/5050/5550/6050	
	15	Lowered Fork Height	h13(mm)	90	
	16	Overall Length	l1(mm)	2010/2020	
	17	Overall Width	b1(mm)	790	
	18	Fork Dimensions	S/e/l(mm)	60/170/1150	
	19	Width over Forks	b5(mm)	570/685	
	20	Aisle Width, with Pallet 1000x1200 Crosswise	Ast(mm)	2900	
	21	Aisle Width, with Pallet 800x1200 Lengthwise	Ast(mm)	2840	
	22	Groud Clearance	m2(mm)	40	
23	Turning Radius		mm	1600	
Performance	24	Speed	Lifting (Laden/unladen)	m/s	/
	25		Falling(Laden/unladen)	m/s	hand control
	26	Max.Gradeabilit v	(Laden/unladen)	%	8/10
	27	Service Weight (include battery)		kg	1050/1220/1185/1350
Driven	28	Service brake			Electromagnetic / Regenerative
	29	Motor	Driven Motor	kw	1.2/1.5
	30		Lift Motor	kw	3.3
	31		Steering Motor Type		Electric
	32	Battery	Voltage/noinal Capacity		V/Ah
33	Size(L×W×H)		mm	650×197×530	