

Carry-up Self-propelled Scissors Lift Platform (Small)

	1	Model		ASF0.3-1.8	ASF0.3-3	ASF0.3-3.9
Specification	2	Platform Height (Max)	mm	1800	3000	3900
	3	Platform Height (Min)	mm	640	720	800
	4	Platform Size	mm	1150×600	1150×600	1150×600
	5	Overall Length	mm	1160	1160	1160
	6	Overall Width	mm	760	760	760
	7	Overall Height	mm	1640	1720	1800
	8	Overall Height (Folding)	mm	1340	1420	1500
	9	Max.Load	kg	300	300	300
	10	Platform Extension	mm	550	550	550
	11	S.W.L On Extension	kg	100	100	100
	12	Elevating Rise Time	S	10	33	53
	13	Elevating Fall Time	S	7	30	50
	14	Ground Clearance (Min)	mm	60	60	60
	15	Turning Radius (Min)	mm	1200	1200	1200
	16	Driving Wheels	mm	Ф230×80	Ф230×80	Ф230×80
	17	Front Wheel	in	6	6	6
	18	Travel Speed	km/h	4	4	4
	19	Betteries	V/Ah	2×12/80	2×12/80	2×12/80
	20	Lifting Motor	V/kw	24/0.8	24/0.8	24/0.8
	21	Drive Motors	V/kw	2×24/0.4	2×24/0.4	2×24/0.4
	22	Integrated Charger	V/A	24/18	24/18	24/18
	23	Weight	kg	600	630	660